



Fiche technique

Climatisation mobile réversible 2,6 kw C-AIRLUX



Manufacturer model no.	C-AIRLUX-1A-09
Features	9000BTU/H for Cooling/Dehumidify/Fan
Technical features	
1. Cooling capacity (W)	2600
2. Cooling power input at the appliance (W)	970
3. Heating capacity (W)	2300 (for option)
4. Heating power input at the appliance (W)	870 (for option)
5. Dehumidify capacity(L/H)	1,2
6. Air Flow volume (m ³ /h)	300
7. Noise during operation (dB (A))	<65
8. Compressor	GMCC
9. Refrigerant	R290(180g)
10. Voltage	220-240
11. Frequency (Hz)	50
12. Application Area(m ²)	12~18m ²
13. Standard - Colours	White/Black
14. Power cord	3*1.0mm ² *1.8M
15. Plug	VDE/BS 3 pins plug
16. Certificate	CE/RoHS/ERP/CB(SGS)
17. Permissible excessive	Discharge 2.6MPa
18. Operating pressure	Suction 1.0MPa
19. Max allowable pressure	Discharge 3.2MPa
	Suction 1.2MPa
20. Rated Current	Cooling 4.3A
	Heating 3.9A
Packing information	
Product dimension (LxWxH, mm)	W330xD292WxH686.5
Packaging dimension (LxWxH, mm)	W370xD325xH860
N.W / G.W (kg)	23.9/25.3
Loading QTY 20'ft/40'GP/ 40' HQ	210/434/650

Accessories included: (Please mark YES or USD price)	YES/ USD
Electronical Panel	YES
Remote Control	YES
Battery	AAA battery*2
Exhaust Pipe	YES, 1.5M
Slid Window Adapter	YES, 2pcs(1.2M)
(Drainage) Water Pipe	Yes, 1M
External (Drainage) Water Tray	Optional
Full colour giftbox (If the order is less than 1000pcs per mod)	Optional, USD 3/PC
Multi-Language Instruction Manual (if more than 3 languages)	USD0.3/Language
Function (please mark YES or NO)	YES/ NO
Auto Restart function	YES
Quiet operation	YES
Fan speed adjustable	YES, 2 speeds
Adjustable vertical exhaust air louvers	YES, Manually
Adjustable horizontal exhaust air louvers	YES, Manually
Casters	YES
Auto Diagnosis	YES
Dust filter	YES
Error display and protection	YES
Power cord storage design	YES
Defrosting	YES
Low Voltage Startup	YES
Independent Dehumidification	YES
Energy-saving Sleep Mode	YES
Temperature selection	YES, 16~31°C
ON Timer	YES/ 24HOUR TIMER
ADVANTAGES	<p>1) Comfortable cooling, strong dehumidifying functions in design. Heater are the optional functions. It can be used as air conditioner, dehumidifier, heater, so you can use it in whole year.</p> <p>2) The temperature difference of cold air inlet and air outlet can reach 10-12degree C. It feels very cold.</p> <p>3) It can be easily moved here and there.</p> <p>4) It can dry the clothes, quilt, socks, etc., and is faster than the normal drier and save the power.</p> <p>5) If the room temperature is not so hot or the room is in good vantilation, you don't connect the exhaust hose. It has a great help for health, especially for kits and old man.</p> <p>6) Ideal product to use in kitchen room, office, study room, living room, etc. as personal air conditioner. You can use it as dehumidifier in office, warehouse,house, computer control room, library,etc.</p> <p>7) The exhaust hose can be connected to the cold side so that this unit can be used as spot cooler for tent,Camps, Animal house, control room, service room, etc.</p> <p>8) The oxygen level and the humidity would not be changed when it is used as air conditioner. It is good for health, specially for children, women, old man, etc.</p> <p>9) No water out when cooling.</p> <p>10) Over-cold prevention function.</p>
<p>Cool&Co 35, rue J-F Kennedy L-7327 STEINSEL Tél : +352 48 90 41 - info@cool-co.lu - www.cool-co.lu</p>	