

FrameFoot® Mini


NEW

HEAT
PUMP
SPECIAL


- > Compact anti-vibration stand
- > Fits particularly well heat pumps
- > Comes complete in 1 single box




Model	FF-755	FF-1250 Mono	FF-1250-VR
Part Nr	0502.00030.000	0502.00030.001	0502.00030.002
Max spread load capacity	360 kg	450 kg	450 kg
Colour	Black grey (7021)	Black grey (7021)	Black grey (7021)
Max unit Width (W) x Depth (D)	755 (29,72") x 520mm (20,47")	1250 (49,21") x 520mm (20,47")	1250 (49,21") x 820mm (32,28")
Min unit Width (W) x Depth (D)	450 (17,72") x 120mm (4,72")	690 (27,16") x 120mm (4,72")	690 (27,16") x 120mm (4,72")
Min - Max height	330 - 370mm (12,99" x 14,57")	330 - 370mm (12,99" x 14,57")	330 - 370mm (12,99" x 14,57")
Inclination (roof)	min. 0° - max. 5°	min. 0° - max. 5°	min. 0° - max. 5°
Packing	1 BOX	1 BOX	1 BOX
Pallet	40 BOX	40 BOX	30 BOX



FF-755



FF-1250 Mono



FF-1250 VR

