



CLIMATISATION MOBILE

2.05 et 2.6 Kw

Phase		Single phase	Single phase
COOLING			
Rated power (min./max.)	kW	2.05	2.64
Rated power input	kW	0.96	120
Current	A	3.3	4.3
EER/Energy label		2,7/A	2.60/A
Operating limits	°C	17°/35° Dry bulb	
INDOOR UNIT			
Type		Monobloc	Monobloc
Sound pressure level to 1m (M S/HS)	dB(A)	47/52	48/52
Sound power Level	dB(A)	63	63
Airflow (M S/HS)	m³/h	213/319	205/295
Diameter flexible emission duct	mm	150	
Length range of heat emission duct	m	0.50 - 1.50	
Dehumidification	l/h	18	2.3
Outline dimensions (WxHxD)	mm	355x345x703	355x345x703
Package dimensions (WxHxD)	mm	400x390x880	400x390x880
Net weight/Gross weight	kg	22,5/25,5	24,7/27,3
Part number		JM B 02 1060	JM B 02 1061
POWER SUPPLY			
Phase/Tension/Frequency		1P/230V/50Hz	1P/230V/50Hz
PIPE LINE			
Refrigerant / GWP		R290/20	R290/20
Charge	kg	0.13	0.17

